



# Guide to Lead Flashing Roll Weights to BS EN 12588

British Lead

Nominal Thickness		CODE 3		CODE 4		CODE 5		CODE 6		CODE 7		CODE 8	
		1.32mm		1.80mm		2.24mm		2.65mm		3.15mm		3.55mm	
Standard Widths		3m	6m	3m	6m	3m	6m	3m	6m	3m	6m	3m	6m
mm	Nearest Imperial	kg	kg	kg	kg	kg	kg	kg	kg	kg	kg	kg	kg
150	6"	7	13	9	18	11	23	14	27	16	32	18	36
180	7"	8	16	11	22	14	27	16	32	19	39	22	43
210	8"	9	19	13	26	16	32	19	38	23	45	25	51
240	9"	11	22	15	29	18	37	22	43	26	51	29	58
300	12"	13	27	18	37	23	46	27	54	32	64	36	72
360	14"	16	32	22	44	27	55	32	65	39	77	43	87
390	15"	18	35	24	48	30	59	35	70	42	84	47	94
450	18"	20	40	28	55	34	69	41	81	48	96	54	109
510	20"	23	46	31	62	39	78	46	92	55	109	62	123
600	24"	27	54	37	73	46	91	54	108	64	129	72	145
760	30"	34	68	47	93	58	116	69	137	81	163	92	184
800	32"	36	72	49	98	61	122	72	144	86	171	97	193
900	36"	40	81	55	110	69	137	81	162	96	193	109	217
1000	40"	45	90	61	122	76	152	90	180	107	214	121	242
1220	48"	55	110	75	149	93	186	110	220	131	261	147	295
1500	60"	67	135	92	184	114	229	135	270	161	321	181	362
2440	96"	-	-	149	299	186	372	220	440	261	523	295	589
Weight per m <sup>2</sup>		15.0kg		20.41kg		25.40kg		30.10kg		35.72kg		40.26kg	

To calculate the approximate weight = Length in metres x Width in metres x Code weight in kg/m<sup>2</sup> as shown above

**PATINATION OIL • LEAD SLATES • POINTING SEALANT • HALL CLIPS • T-PREN • UNDERLAYS**

British Lead, Peartree Lane, Welwyn Garden City, Herts AL7 3UB [www.britishlead.co.uk](http://www.britishlead.co.uk)

**FREEPHONE: 0800 117882**  
**FREEFAX: 0800 575092**